

BASES EMPOTRABLES - IP66/IP67

Serie EUREKA									
		417.	(•)	427.					
Polos	Hz.	Voltios	Color	h.	INCLINADA BRIDA DE FIJACIÓN NORMAL		RECTA BRIDA DE FIJACIÓN REDUCIDA 75x75		
					16A	32A	16A	32A	
2P+T	50/60	100-130	■	4	417.1660	417.3260	427.1660	427.3260	
	50/60	200-250	■	6	417.1663	417.3263	427.1663	427.3263	
	50/60	380-415	■	9	417.1668	417.3268	427.1668	427.3268	
	50/60	480-500	■	7	427.16636		427.16636	427.32636	
	50/60	trasf.	■	12	427.16633		427.16633	427.32633	
	>300-500	>50	■	2	427.16632		427.16632	427.32632	
3P+T	c.c.	>50-250	■	3	427.16634		427.16634	427.32634	
	c.c.	>250	■	8	427.16638		427.16638	427.32638	
	50/60	100-130	■	4	417.1661	417.3261	427.1661	427.3261	
	50/60	200-250	■	9	417.1664	417.3264	427.1664	427.3264	
	50/60	380-415	■	6	417.1666	417.3266	427.1666	427.3266	
	60	440-460	■	11			427.16665	427.32665	
3P+N+T	50/60	480-500	■	7	427.16666		427.16666	427.32666	
	50/60	600-690	■	5	427.16667		427.16667	427.32667	
	50	380	■	3	427.16664		427.16664	427.32664	
	60	440	■	10	427.16661		427.16661	427.32661	
	>300-500	>50	■	2	427.16662		427.16662	427.32662	
	50/60	100-130	■	4	417.1662	417.3262	427.1662	427.3262	
3P+N+T	50/60	208-250	■	9	417.1665	417.3265	427.1665	427.3265	
	50/60	346-415	■	6	417.1667	417.3267	427.1667	427.3267	
	50/60	480-500	■	7			427.16676	427.32676	
	50/60	600-690	■	5			427.16677	427.32677	
	60	440-460	■	11			427.16675	427.32675	
	50	380	■	3	427.16674		427.16674	427.32674	
3P+N+T	>300-500	>50	■	2	427.16672		427.16672	427.32672	

Tensión nominal >50V
-Aprobaciones: de pág. 561

- Borres de tornillo
 - Borres de resorte
- Más información de pág. 36



■ De color negro
Versiones también disponible en negro: sólo agregar "K" al final de cada referencia
Ejemplo: 418.1663 K

Serie EUREKA									
		457.	(•)	418.	(•)	415.	Serie OPTIMA		
Polos	Hz.	Voltios	Color	h.	CON SALIDA A 90°		INCLINADA BRIDA DE FIJACIÓN NORMAL		INCLINADA BRIDA DE FIJACIÓN NORMAL
					16A	32A	16A	32A	
2P+T	50/60	100-130	■	4	457.1660	457.3260	418.1660H	418.3260F	415.6360
	50/60	200-250	■	6	457.1663	457.3263	418.1663H	418.3263F	415.6363
	50/60	380-415	■	9	457.1668	457.3268	418.1668H	418.3268F	415.6368
	50/60	480-500	■	7	457.16636	457.32636			415.63636
	50/60	trasf.	■	12	457.16633	457.32633			415.63633
	>300-500	>50	■	2	457.16632	457.32632			415.63632
3P+T	c.c.	>50-250	■	3	457.16634	457.32634			415.63634
	c.c.	>250	■	8	457.16638	457.32638			415.63638
	50/60	100-130	■	4	457.1661	457.3261			415.6361
	50/60	200-250	■	9	457.1664	457.3264			415.6364
	50/60	380-415	■	6	457.1666	457.3266			415.6366
	60	440-460	■	11					415.63665
3P+N+T	50/60	480-500	■	7	457.16666	457.32666			415.63666
	50/60	600-690	■	5	457.16667	457.32667			415.63667
	50	380	■	3	457.16664	457.32664			415.63664
	60	440	■	10	457.16661	457.32661			415.63661
	>300-500	>50	■	2	457.16662	457.32662			415.63662
	50/60	100-130	■	4	457.1662	457.3262			415.6362
3P+N+T	50/60	208-250	■	9	457.1665	457.3265			415.6365
	50/60	346-415	■	6	457.1667	457.3267			415.6367
	50/60	480-500	■	7					415.63676
	50/60	600-690	■	5					415.63677
	60	440-460	■	11					415.63675
	50	380	■	3	457.16674	457.32674			415.63674
3P+N+T	>300-500	>50	■	2	457.16672	457.32672			415.63672

⁽¹⁾ 2P+E= 10/60

● Ideales para cuadro Serie DOMINO (pág. 137)
y Serie BLOCK (pág. 144)



Accesorios
Cajas vacías para realizar versiones murales
pág. 60