

PROLONGADORES - IP66/IP67

Serie EUREKA

1

INDUSTRIA



2

3

4

316.

326.



									CON SALIDA A 90°	
Polos	Hz.	Voltios	Color	h.	16A	32A	16A	32A		
					prensaestopa 10/100 ⁽¹⁾	prensaestopa 10/40	prensaestopa 10/100 ⁽¹⁾	prensaestopa 10/40		
2P+T	50/60	100-130		4	316.1640 (Δ)	316.3240	326.1640	326.3240		
	50/60	200-250		6	316.1643 (Δ)	316.3243	326.1643	326.3243		
	50/60	380-415		9	316.1648	316.3248				
	50/60	480-500		7						
	50/60	trasf.		12						
	>300-500	>50		2						
	c.c.	>50-250		3						
	c.c.	>250		8						
3P+T	50/60	100-130		4	316.1641	316.3241				
	50/60	200-250		9	316.1644	316.3244				
	50/60	380-415		6	316.1646	316.3246	326.1646	326.3246		
	60	440-460		11						
	50/60	480-500		7						
	50/60	600-690		5						
	50/60	380-440		3				326.32464		
	100-300	>50		10						
	>300-500	>50		2						
3P+N+T	50/60	100-130		4	316.1642	316.3242				
	50/60	208-250		9	316.1645	316.3245				
	50/60	346-415		6	316.1647	316.3247	326.1647	326.3247		
	50/60	480-500		7						
	50/60	600-690		5						
	60	440-460		11						
	50/60	380-440		3						
	>300-500	>50		2						

⁽¹⁾ 3P+N+T= 10/40

⁽¹⁾ 3P+N+T= 10/50

Tensión nominal >50V
-Aprobaciones de pag. 561

-  Borries de tornillo
-  Borries de perforación del aislante
-  Borries de resorte

Más información de pag. 36



(Δ) De color negro
Versiones también disponible
en negro, sólo agregar "K" al
final de cada referencia
Ejemplo: 313.1643.K

Serie OPTIMA

318.



										SAFE-IN		FAST WIRING			
											16A		16A		
16A	prensaestopa 10/40	32A	prensaestopa 10/40	63A	prensaestopa 6/24	125A	prensaestopa 1/8			16A	prensaestopa 10/40	16A	prensaestopa 10/40	32A	prensaestopa 10/40
318.1640 (Δ)		318.3240		318.6340		318.12540		318.1640H		318.1640P (Δ)		318.3240F			
318.1643 (Δ/Δ)		318.3243 (Δ)		318.6343		318.12543		318.1643H (Δ)		318.1643P (Δ/Δ)		318.3243F (Δ)			
318.1648		318.3248		318.6348		318.12548		318.1648H		318.1648P		318.3248F			
318.16436		318.32436		318.63436											
318.16433		318.32433		318.63433											
318.16432		318.32432													
318.16434		318.32434		318.63434											
318.16438		318.32438		318.63438											
318.1641		318.3241		318.6341		318.12541									
318.1644		318.3244		318.6344		318.12544		318.1644H		318.1644P		318.3244F			
318.1646 (Δ)		318.3246 (Δ)		318.6346		318.12546		318.1646H (Δ)		318.1646P (Δ)		318.3246F (Δ)			
318.16465		318.32465		318.63465		318.125465									
318.16466		318.32466		318.63466		318.125466									
318.16467		318.32467		318.63467		318.125467									
318.16464		318.32464										318.32464F			
318.16461		318.32461													
318.16462		318.32462													
318.1642		318.3242		318.6342		318.12542									
318.1645		318.3245		318.6345		318.12545									
318.1647 (Δ)		318.3247 (Δ)		318.6347		318.12547		318.1647H (Δ)		318.1647P (Δ)		318.3247F (Δ)			
318.16476		318.32476		318.63476		318.125476									
318.16477		318.32477		318.63477		318.125477									
318.16475		318.32475		318.63475		318.125475									
318.16474		318.32474													
318.16472		318.32472													



(Δ) Mango transparente
Versiones también disponible en transparente;
sólo agregar "TR" al final de cada referencia
Ejemplo 311.1643.TR.