

Rigid Conduit Coupling

Rigid conduit coupling is manufactured from high strength seamless steel pipe in accordance with the standard of ANSI C80.1(UL6). We can provide electro-galvanized coupling or double corrosion resistance with hot-dip galvanized coupling shell and electro-galvanized totally after threaded.

The coupling is produced in normal sizes from 1/2" to 6"

The couplings is used to connect the conduit to extend the length of the conduit .



**Dimension and Packing Chart**

Trade Size	Weight Per 100 pcs(KG)	Weight Per 100 pcs(Lbs)	Outside Diameter "B" (mm)	Minimum Acceptable Length "A"(mm)	Standard Carton Qty	Weight Per Carton(KG)
1/2"	6.35	14	25.7	41.3	100	6.35
3/4"	9.07	20	31.8	41.7	50	4.54
1"	14.06	31	38.7	50.0	50	7.03
1-1/4"	17.69	39	47.5	51.6	50	8.85
1-1/2"	25.40	56	54.7	52.4	50	12.70
2"	33.11	73	67.3	54.0	20	6.62
2-1/2"	83.92	185	82.6	81.0	12	10.07
3"	102.51	226	98.3	84.1	12	12.30
3-1/2"	162.39	358	114.3	86.5	12	19.49
4"	181.44	400	123.8	89.3	12	21.77
5"	225.44	497	152.4	100.4	BULK	2.25
6"	370.10	816	182.9	108.0	BULK	3.70

14

EastConduit Products

UL File No.: E308290(177709-001)

**ISO9001
CERTIFIED**