


1. USE

Cable for high-speed VDI transmission networks

802.3 bt PoE++ applications compatible according to installation standards ISO/IEC 14763-2 (final draft) and EN 50174-2 : 2018

2. DESCRIPTION



3. MARKING AND PACKAGING

Marking of Legrand cables

- LEGRAND
- Catalogue number
- Number of pairs
- Gauge
- Type
- Impedance
- Type of sleeve
- Category
- Conformity to standards
- EUROCLASS
- Velocity of propagation
- Traceability
- Measurement (remaining length in metres).

Complementary marking (on label)

- Designation
- Made in....

4. PERFORMANCE AT 500 MHZ (STAND. ANSI/TIA 568.2-D)

Reference	0 327 87
Maximum attenuation (dB/100 m)	45,3
Minimum NEXT (dB)	33,8
PS NEXT (dB)	31,8
ACRF (dB / 100 m)	13,8
PS ACRF (dB / 100 m)	24,2
Return Loss (dB)	15,2

5. TECHNICAL AND MECHANICAL FEATURES

Catalogue number	0 327 87
Type	U/UTP
Type of sleeve	LSZH
Number of pairs	4
Assembly	Pairs
Diameter over insulation (mm)	1,03±0,1
Average nominal diameter of the cable (mm)	8,3±0,7
Weight of cable (kg/km)	64
Min. bending radius when laying (mm)	70
AWG gauge*	23

* According to UL 444 ed.3 table 4

6. ELECTRICAL FEATURES AT 20°C

Catalogue number	0 327 87
Type	U/UTP
Maximum linear resistance (ohm/km)	86*
DC dielectric strength	1 KV / 1 min *
Minimum insulation resistance (Mohm.km)	5000
Minimum propagation speed	64%
Characteristic impedance at 100 MHz	100 ±5Ω

* According to standard IEC 61156-5

7. ORDERING INFORMATION

Catalogue number	0 327 87
Type	U/UTP
Colour	Yellow RAL 1018
Pack (m)	500
Packaging	Reel

8. ENVIRONMENTAL FEATURES

Transport and storage temperature: 0 at + 50 °C

Storage temperature before use: 10°C during 24h (if stock ≤ 5°C)

Usage temperature: – 20 to + 60 °C

Fire rating:EN 50399, IEC 60332-1-2, EN 60332-1-2

Smoke density : IEC 61034-2, EN 61034-2

Toxicity of fire effluent : IEC 60754-2, EN 60754-2

EUROCLASS EN 13501-6 = Class Dca s2d2a1

Also compliant with Eca

9. STANDARDS AND APPROVALS

Cat 6, 500 MHz

Electrical performances and characteristics :

- ANSI/TIA 568.2-D

- EN 50173-1

- EN 50288-10-1

- ISO/IEC 11801

- IEC 61156-5

IEEE 802.3bt : PoE++