


# Data sheet

Part No.	<b>HFS LG</b>
Description	saddle, with two fixing holes, halogen-free for mounting of rigid or pliable conduits with screws Ø 4 mm
Colour	light grey, similar to RAL 7035

Standard: EN 61386-1, EN 61386-25, EN 60754, EN 50642



Working temperature

-25 to +90 °C

Art. No.	For tube diameter	PU	PU
080812	20 mm	50 pc	1600 pc
080813	25 mm	100 pc	1600 pc
080814	32 mm	100 pc	800 pc
080815	40 mm	50 pc	400 pc
080816	50 mm	50 pc	400 pc
080817	63 mm	25 pc	200 pc

## Further technical details

### Details

Closed	True
Tackable	False
Max. number of tubes	1
Type of fastening	Screw hole
With inlay	False
Material	Plastic

Cardboard packaging used is made from 100% waste paper and is fully recyclable, plastic packaging is fully recyclable.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, [www.dietzel-univolt.com](http://www.dietzel-univolt.com), makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.